

# Dilators

Radiopaque polyethylene dilators feature smooth rounded tips with gradual tapering facilitating tissue penetration.

- Perfect tapering improves tissue penetration.
- Luer lock hub for contrast injection and guidewire exchange.
- Radiopaque for fluoroscopic visualization.

## Dilators

Box of 10

<b>6104 35 020</b>	4F x 20 cm, accepts guidewire .035" (0.89 mm)
<b>6105 35 020</b>	5F x 20 cm, accepts guidewire .035" (0.89 mm)
<b>6105 38 020</b>	5F x 20 cm, accepts guidewire .038" (0.97 mm)
<b>6106 35 020</b>	6F x 20 cm, accepts guidewire .035" (0.89 mm)
<b>6106 38 020</b>	6F x 20 cm, accepts guidewire .038" (0.97 mm)
<b>6107 35 020</b>	7F x 20 cm, accepts guidewire .035" (0.89 mm)
<b>6107 38 020</b>	7F x 20 cm, accepts guidewire .038" (0.97 mm)
<b>6108 35 020</b>	8F x 20 cm, accepts guidewire .035" (0.89 mm)
<b>6108 38 020</b>	8F x 20 cm, accepts guidewire .038" (0.97 mm)
<b>6109 38 025</b>	9F x 25 cm, accepts guidewire .038" (0.97 mm)
<b>6110 38 025</b>	10F x 25 cm, accepts guidewire .038" (0.97 mm)
<b>6112 38 025</b>	12F x 25 cm, accepts guidewire .038" (0.97 mm)
<b>6114 38 025</b>	14F x 25 cm, accepts guidewire .038" (0.97 mm)
<b>6116 47 025</b>	16F x 25 cm, accepts guidewire .047" (1.19 mm)



61xx

# Screw Dilators

A screw dilator atraumatically separates tissue, allowing dilation up to 14 French by using only one dilator.

- Minimal patient discomfort.
- Blunt dissection.
- Minimises risk of guidewire dislocation.
- Tissue dilation up to 14F using only one dilator.
- Radiopaque for fluoroscopic visualization.



A wide range of French sizes

## Screw Dilators

Box of 10

<b>6307 38 025</b>	7F x 25 cm, accepts guidewire .038" (0.97 mm)
<b>6308 38 025</b>	8F x 25 cm, accepts guidewire .038" (0.97 mm)
<b>6309 38 025</b>	9F x 25 cm, accepts guidewire .038" (0.97 mm)
<b>6310 38 025</b>	10F x 25 cm, accepts guidewire .038" (0.97 mm)
<b>6312 38 025</b>	12F x 25 cm, accepts guidewire .038" (0.97 mm)
<b>6314 38 025</b>	14F x 25 cm, accepts guidewire .038" (0.97 mm)
<b>6316 47 025</b>	16F x 25 cm, accepts guidewire .047" (1.19 mm)
<b>6318 52 025</b>	18F x 25 cm, accepts guidewire .052" (1.32 mm)

63xx

