

The SKATER® Drainage Catheter is made of soft polyurethane for optimal kink resistance and perfect configuration memory. The catheter is coated with HYDROFEEL® hydrophilic coating for minimal friction during insertion.

- Soft polyurethane for optimal kink resistance and perfect configuration memory.
- HYDROFEEL® coating on distal part for easy insertion.
- Large oval drainage holes and large lumen are designed for maximal drainage capacity.
- Minimal tissue trauma and ulcerations reduce patient discomfort.
- With locking or non-locking pigtail.



SKATER® Drainage Catheter • with locking pigtail **Box of 5**

7551 06 025	6F x 25 cm, accepts guidewire .035" (0.89 mm), metal stiffening cannula
7551 06 035	6F x 35 cm, accepts guidewire .035" (0.89 mm), metal stiffening cannula
7551 07 025	7F x 25 cm, accepts guidewire .035" (0.89 mm), metal stiffening cannula
7551 07 035	7F x 35 cm, accepts guidewire .035" (0.89 mm), metal stiffening cannula
7551 08 025	8F x 25 cm, accepts guidewire .038" (0.97 mm), metal and flexible stiffening cannulae
7551 08 035	8F x 35 cm, accepts guidewire .038" (0.97 mm), metal and flexible stiffening cannulae
7551 10 025	10F x 25 cm, accepts guidewire .038" (0.97 mm), metal and flexible stiffening cannulae
7551 10 035	10F x 35 cm, accepts guidewire .038" (0.97 mm), metal and flexible stiffening cannulae
7551 12 025	12F x 25 cm, accepts guidewire .038" (0.97 mm), metal and flexible stiffening cannulae
7551 12 035	12F x 35 cm, accepts guidewire .038" (0.97 mm), metal and flexible stiffening cannulae
7551 14 025	14F x 25 cm, accepts guidewire .038" (0.97 mm), metal and flexible stiffening cannulae
7551 14 035	14F x 35 cm, accepts guidewire .038" (0.97 mm), metal and flexible stiffening cannulae
7551 16 025	16F x 25 cm, recommended guidewire .038" (0.97 mm), metal and flexible stiffening cannulae

SKATER® Drainage Catheter • with non-locking pigtail **Box of 5**

7511 06 025	6F x 25 cm, accepts guidewire .035" (0.89 mm), metal stiffening cannula
7511 06 035	6F x 35 cm, accepts guidewire .035" (0.89 mm), metal stiffening cannula
7511 07 025	7F x 25 cm, accepts guidewire .035" (0.89 mm), metal stiffening cannula
7511 07 035	7F x 35 cm, accepts guidewire .035" (0.89 mm), metal stiffening cannula
7511 08 025	8F x 25 cm, accepts guidewire .038" (0.97 mm), metal and flexible stiffening cannulae
7511 08 035	8F x 35 cm, accepts guidewire .038" (0.97 mm), metal and flexible stiffening cannulae
7511 10 025	10F x 25 cm, accepts guidewire .038" (0.97 mm), metal and flexible stiffening cannulae
7511 10 035	10F x 35 cm, accepts guidewire .038" (0.97 mm), metal and flexible stiffening cannulae
7511 12 025	12F x 25 cm, accepts guidewire .038" (0.97 mm), metal and flexible stiffening cannulae
7511 12 035	12F x 35 cm, accepts guidewire .038" (0.97 mm), metal and flexible stiffening cannulae
7511 14 025	14F x 25 cm, accepts guidewire .038" (0.97 mm), metal and flexible stiffening cannulae
7511 16 025	16F x 25 cm, recommended guidewire .038" (0.97 mm), metal and flexible stiffening cannulae

SKATER® Biliary Drainage Catheters

SKATER® catheter for drainage of the bile duct using the Sel-dinger technique. The catheter is made of soft polyurethane for optimal kink resistance and perfect configuration memory.

- Soft polyurethane for optimal kink resistance and perfect configuration memory.
- HYDROFEEL® coated on the distal tip for easy insertion.
- Non-kinking and flexible stylet included.
- Large oval drainage holes and large lumen designed for optimal drainage capacity. 4 side holes in pigtail and 7 or 8 side holes on the shaft.
- Minimal tissue trauma and ulcerations reduce patient discomfort.

Box of 5

SKATER® Biliary Drainage Catheter • with locking pigtail

7553 08 040	8F x 40 cm, accepts guidewire .038" (0.97 mm), metal and flexible stiffening cannula
7553 10 040	10F x 40 cm, accepts guidewire .038" (0.97 mm), metal and flexible stiffening cannula
7553 12 040	12F x 40 cm, accepts guidewire .038" (0.97 mm), metal and flexible stiffening cannula

Box of 5

SKATER® Biliary Drainage Catheter • with non-locking pigtail

7552 08 040	8F x 40 cm, accepts guidewire .038" (0.97 mm), metal and flexible stiffening cannula
7552 10 040	10F x 40 cm, accepts guidewire .038" (0.97 mm), metal and flexible stiffening cannulae
7552 12 040	12F x 40 cm, accepts guidewire .038" (0.97 mm), metal and flexible stiffening cannulae

7553

